

# Onyx<sup>®</sup> 3

## *Finger Pulse Oximeter*



## Cutting Edge Technology You Can Trust

Meet Nonin's new Onyx3 Finger Pulse Oximeter; now including respiratory rate. You can trust Nonin Medical's Onyx3 using PureSAT<sup>®</sup> technology to quickly and accurately capture SpO<sub>2</sub>, pulse rate, and respiratory rate measurements — even on patients where low perfusion is a challenge. Reliability matters, and Onyx3 provides accurate data for actionable decision making.

## Added Benefits

- Multicolor LCD – SpO<sub>2</sub>, pulse rate, and respiration rate display
- Wireless BLE connectivity
- Quickly and accurately accommodates fingers, thumbs and toes with digit thicknesses: 8 mm to 25.4 mm (0.3" to 1.0").
- The auto-on/off mechanism allows two AAA batteries to provide up to 2,000 spot checks before being replaced.



## Product Highlights

- Clinician-facing, easy-to-read multicolor display.
- Wireless patient data at the tip of your finger.
- Nonin CorrectCheck– Gives feedback when the finger is not placed properly in the device.
- Automatically adjusts to each patient from pediatric to adult.
- Automatically turns on and off - Just insert digit for fast and easy spot checks.
- Portable – Take the Onyx3 anywhere — weighing only two ounces
- Signal Quality Indicator provides a quick assessment of patient pulse quality.



## Specifications

<b>Dimensions</b> .....	56.7mm (2.23") L x 33.4mm (1.31") W x 33mm (1.30") H
<b>Respiratory Rate Accuracy</b> .....	+/- 1 breath per minute
<b>Warranty</b> .....	2 years
<b>Oxygen Saturation Display Range</b> .....	0 – 100% SpO <sub>2</sub>
<b>Pulse Rate Display Range</b> .....	18 – 321 beats per minute (BPM)
<b>Oxygen Saturation Declared Accuracy Range (Arms*)</b> .....	70 – 100% SpO <sub>2</sub> ±2 digits
<b>Low Perfusion Oxygen Saturation Declared Accuracy Range (Arms*)</b> .....	70 – 100% SpO <sub>2</sub> ±2 digits
<b>Pulse Rate Declared Accuracy Range (Arms*)</b> .....	20 – 250 BPM ±3 digits
<b>Low Perfusion Pulse Rate Declared Accuracy Range (Arms*)</b> .....	40 – 240 BPM ±3 digits
<b>Measurement Wavelengths and Output Power**</b>	
Red .....	660 nanometers @ 0.8 mW maximum average
Infrared .....	910 nanometers @ 1.2 mW maximum average
<b>Temperature</b>	
Operating .....	-5° to +40°C (+23° to +104°F)
Storage/Transportation .....	-40° to +70°C (-40° to +158°F)
<b>Humidity</b>	
Operating .....	10 – 90% non-condensing
Storage/Transportation .....	10 – 95% non-condensing
<b>Altitude</b>	
Operating .....	0-4,000m (13,123ft)
<b>Hyperbaric Pressure</b> .....	Up to 4 atmospheres
<b>Battery Life</b>	
Operating.....	2,000 spot checks (25 hours)
Storage.....	1 month

Classifications per IEC 60601-1 / CAN/CSA-C22.2 No. 601.1 / UL 60601-1:

Degree of Protection .....	Type BF-Applied Part
Mode of Operation .....	Continuous
Enclosure Degree of Ingress Protection .....	IP32

This product complies with ISO 10993-1, Biological evaluation of medical devices – Part 1: Evaluation and testing.

\*±1 A<sub>rms</sub> represents approximately 68% of measurements.

\*\*This information is especially useful for clinicians performing photodynamic therapy.

Specifications are subject to change without notice.

## Your Partner of Choice.

With more than 25 years of experience and dedication to the design and support of noninvasive monitoring devices, Nonin Medical has helped many medical professionals meet clinical and economic objectives. More than 100 OEM partners around the world rely on Nonin's digital technology to successfully integrate superior pulse oximetry and capnography into their products.



**Nonin Medical, Inc.**  
13700 1st Avenue North  
Plymouth, MN • 55441-5443 • U.S.A.  
**Tel:** +1.763.553.9968 1.800.356.8874  
**Fax:** +1.763.577.5521  
**E-mail:** info@nonin.com

[nonin.com/oemSolutions](http://nonin.com/oemSolutions)

**Nonin Medical B.V.**  
Prins Hendriklaan 26  
1075 BD Amsterdam • Netherlands  
**Tel:** +31 (0)13-79 99 040  
**Fax:** +31 (0)13-79 99 042  
**E-mail:** infointl@nonin.com

